

# NORBOND®

## OP7

Providing durable, long-lasting security

## Finish Blocking Pad for General Use

Saint-Gobain NORBOND® OP7 is an economic, yet reliable, performing blocking pad for general use. It is constructed with a strong polyurethane foam that is engineered to resist the rotational forces resulting from the edging process. With strong acrylic adhesive on both sides, it will not slip during the edging process, yet removes cleanly with no residue or adhesive marring. OP7 is provided with a silicone-coated paper liner that allows for easy die-cutting.

NORBOND OP7 is specially designed to provide the following features:


- Strong polyurethane foam core assures a precise hold
- Acrylic adhesive on both sides for good quick-stick and clean removal
- Flexible and conformable for good wet-out to a wide range of lens curvatures
- Economic alternative for non-super hydrophobic lens coatings

### Available Sizes

Standard thickness: .031 in.

Master roll size: 54 in. (1372 mm) width. Length varies with thickness.

Slit rolls also available.



### Applications

- Blocking pads for optical lens edging

## NORBOND® OP7 – Properties

(Formerly known as SecurEdge)

Performance tests are run using standard test procedures. The values presented are typical values and should not be used for specification purposes.

| Property  | Typical Value |
|---|---------------|
| Density: lb/ft <sup>3</sup> (kg/m <sup>3</sup> )                            | 33 (530)      |
| Dynamic Shear Adhesion: 20 min. dwell<br>Stainless steel overlap: psi (kPa) | 134 (924)     |
| 90° Peel Adhesion: coated lens lbs/in. (N/cm)                               | .59 (1.03)    |

## Liners

A white or blue paper liner is standard.

## Important Instructions

- Because Saint-Gobain cannot anticipate or control every potential application, we strongly recommend testing of this product under individual application conditions prior to commercial use.
- Surfaces must be clean and free of oil, grease, moisture, dust and dirt. Isopropyl alcohol is good for cleaning the surface.
- Apply a uniform pressure of 15 psi (103 kPa) to promote good contact between the material to be bonded and the tape. The application temperature should be between 60°F and 125°F (16°C to 52°C). It is not recommended to apply these tapes at temperatures below 60°F (16°C), as the adhesive does not flow in this condition and can result in poor bonding.
- Recommended service temperature is between -40°F to 200°F (-40°C to 93°C).
- The adhesion between the substrate and the tape increases with time, typically reaching final bond strength in 72 hours. Heating the product above 105°F (40°C) will accelerate the adhesion process.

## Shelf Life

12 months after the date of sale when stored in original packaging at temperatures up to 70°F (21°C) and 50% relative humidity.

NORBOND® is a registered trademark of Saint-Gobain Performance Plastics.



### Saint-Gobain Performance Plastics

One Sealants Park  
Granville, NY 12832

1-800-724-0883  
Tel: (518) 642-2200  
Fax: (518) 642-2793

[foams@saint-gobain.com](mailto:foams@saint-gobain.com)  
[www.foams.saint-gobain.com](http://www.foams.saint-gobain.com)

The data and details in this document were correct and up-to-date at the time of printing and are intended to provide information on our products and their possible applications. It is the user's responsibility to obtain the latest version of the product data sheet. This data sheet is not a specification and does not assure specific product characteristics or make reference to the suitability of the product for a specific application. Because Saint-Gobain cannot anticipate or control every application, we strongly recommend testing of this product under individual application conditions. The application, use and conversion of this product are the user's responsibility.

Limited Warranty: For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse, or inability to use this product(s).

SAINT-GOBAIN PERFORMANCE PLASTICS DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

NOTE: Saint-Gobain Performance Plastics Corporation does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s) or of any final product into which the product(s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform its own tests to determine the suitability and fitness of the product(s) for the particular purpose desired in any given situation.

## NORBOND® OP7– Standard Roll Sizes

| Product No. | Thickness in. (mm) | Length ft. (m) |
|-------------|--------------------|----------------|
| OP7         | .031 (.8)          | 216 (65)       |
| OP7         | .031 (.8)          | 432 (131)      |